

HENDRICKSON USE ONLY

Kit Part No.:

Kit Price:

ORDERING GUIDE
TIREMAAX® TIRE INFLATION SYSTEM

LIT NO: L868

DATE: December 2020

REVISION: Q

FORM INSTRUCTIONS

For complete price and model number information for a TIREMAAX® system, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO:		FROM:		COMPANY NAME:	
DATE:	PHONE:	FAX:	EMAIL:		

SAME AS:	EXCEPT:
-----------------	----------------

TIREMAAX®¹ (Continued on page 2)

CONTROLLER TYPE:	<input type="checkbox"/> CP	<input type="checkbox"/> PRO
ELECTRICAL CONNECTION:	<input type="checkbox"/> Delphi Weather Pack (Standard)	<input type="checkbox"/> Blade Terminals ²
KIT STYLE:	<input type="checkbox"/> For OEM Installation	<input type="checkbox"/> For Aftermarket / Retrofit Installation
AXLE STYLE:	<input type="checkbox"/> Integrated (INTRAAX®, VANTRAAX®, etc.)	
	<input type="checkbox"/> Standard (Hendrickson TRLAXLE®)	Standard Axle Track: <input type="checkbox"/> 71.5" to 83" <input type="checkbox"/> 83.5" to 92"
AXLE PREPARATION:	<input type="checkbox"/> TIREMAAX Prepped / Wheel-ends Installed by Hendrickson (Kit includes controller and tire hoses only.) <input type="checkbox"/> TIREMAAX Prepped / Wheel-ends Installed by Trailer OEM (Kit includes controller, hubcap assemblies and tire hoses.) <input type="checkbox"/> Not Prepped for TIREMAAX (Select for Aftermarket / Retrofit applications; Kit includes controller, hubcap assemblies, tire hoses and axle kit.)	
NUMBER OF AXLES:	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> Other:	
SPINDLE STYLE:	<input type="checkbox"/> HN <input type="checkbox"/> HP	
HUBCAP TYPE:	<input type="checkbox"/> Hendrickson Bolt-On	<input type="checkbox"/> Hendrickson Extended Bolt-On ³
LUBE TYPE:	<input type="checkbox"/> Semi-Fluid Grease	<input type="checkbox"/> Oil
WHEEL STYLE / MATERIAL:	<input type="checkbox"/> Dual / Aluminum <input type="checkbox"/> Dual / Steel or Combo <input type="checkbox"/> Super Single / Aluminum (straight hose) <input type="checkbox"/> Super Single / Steel (outboard valve stem; 180-degree hose) <input type="checkbox"/> Super Single / Steel (inboard valve stem; straight hose)	
TIRE SIZE:	<input type="checkbox"/> 17.5" <input type="checkbox"/> 19.5" <input type="checkbox"/> 22.5" <input type="checkbox"/> 24.5"	
COLD TIRE PRESSURE SETTING (psi)⁴:	<input type="checkbox"/> 70 <input type="checkbox"/> 75 <input type="checkbox"/> 80 <input type="checkbox"/> 85 <input type="checkbox"/> 90 <input type="checkbox"/> 95 <input type="checkbox"/> 100 <input type="checkbox"/> 105 <input type="checkbox"/> 110 <input type="checkbox"/> 115 <input type="checkbox"/> 120	

- Hendrickson does not provide warranty coverage for the installation, performance or components of a competitor brand tire inflation system installed on a Hendrickson suspension or trailer axle. Any consequential damages to the Hendrickson suspension or trailer axle resulting from a failure to the competitor brand tire inflation system or components, whether installed by the OEM, repair facility or end-user customer, should be directed to the respective tire inflation system manufacturer for warranty coverage.
- Controllers featuring blade terminals, require the light kit and wiring harness options to be "no".
- Required for axles with TIREMAAX PRO equipped with cross-drilled spindles and using the castellated spindle nut. Please verify spindle nut requirements.
- Refer to tire manufacturer's recommended tire pressure. TIREMAAX PRO is restricted to cold tire pressure setting of 85-120 psi.



TIREMAAX®*(Continued from page 1)*

TIRE HOSE:	<input type="checkbox"/> Standard	<input type="checkbox"/> Integral Check Port (22.5" tire size only)
TRAILER-MOUNTED INDICATOR LIGHT KIT:	<input type="checkbox"/> LED – 12V with 65-foot Cable (Standard) <input type="checkbox"/> Incandescent – 12V	<input type="checkbox"/> LED – 12V with 35-foot Cable <input type="checkbox"/> LED – 24V (Export ⁵) <input type="checkbox"/> No ²
WIRING HARNESS:	<input type="checkbox"/> Premium, 15-Foot, ABS-ready <input type="checkbox"/> Standard, 18-inch, Wiring Adapter Plug	<input type="checkbox"/> Premium, 3-Foot, ABS-ready <input type="checkbox"/> No ²
AIR PLUMBING KIT:	<input type="checkbox"/> Manifold ⁶	<input type="checkbox"/> No
CONTROLLER TANK VALVE⁷: (Pressure Check)	<input type="checkbox"/> Yes (CP Models Only)	<input type="checkbox"/> No

5. Please note, 12V is used in some export countries. If this is a new venture into a foreign country, please validate voltage requirements with Controls Engineering.

6. Not available for single-axle systems.

7. Not available with TIREMAAX PRO.

*Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.
All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.
Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.*

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

L868 Rev Q 12-20

© 2004 - 2020 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries. Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada

250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
800.668.5360
905.789.1030 • Fax 905.789.1033

Hendrickson Mexicana

Círculo El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601